



# 74AVC4T245 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

## GENERAL DESCRIPTION

The 74AVC4T245 is a 4-bit, dual-supply voltage level transceiver with 3-state outputs and bidirectional level translation. The device can be used as two 2-bit transceivers or one 4-bit transceiver. The nAn and nBn are four data input-output ports. nDIR are the direction control inputs and n $\overline{OE}$  are the output enable inputs. V<sub>CCA</sub> and V<sub>CCB</sub> are the supply pins. The supply voltage of V<sub>CCA</sub> and V<sub>CCB</sub> can range from 0.8V to 3.6V, making the device suitable for bidirectional translating among any of the 0.8V, 1.2V, 1.5V, 1.8V, 2.5V and 3.3V voltage nodes. The nAn, nDIR and n $\overline{OE}$  signals are referenced to V<sub>CCA</sub> and nBn signals are referenced to V<sub>CCB</sub>.

When nDIR is set high, it allows transmission from nAn to nBn. When nDIR is set low, it allows transmission from nBn to nAn. n $\overline{OE}$  can be used to make the outputs disabled so that the buses are effectively isolated. In suspend mode, both nAn and nBn are in high-impedance state when either V<sub>CCA</sub> or V<sub>CCB</sub> input is at GND level.

This device is highly suitable for partial power-down applications using power-off leakage current (I<sub>OFF</sub>) circuit. When the device is powered down, the current backflow will be prevented from passing through the device.

## FEATURES

- V<sub>CCA</sub> Supply Voltage Range: 0.8V to 3.6V
- V<sub>CCB</sub> Supply Voltage Range: 0.8V to 3.6V
- Inputs Accept Voltages up to 3.6V
- +12mA/-12mA Output Current
- Data Rates:
  - ◆ 380Mbps (≥ 1.8V to 3.3V Translation)
  - ◆ 200Mbps (≥ 1.1V to 3.3V Translation)
  - ◆ 200Mbps (≥ 1.1V to 2.5V Translation)
  - ◆ 200Mbps (≥ 1.1V to 1.8V Translation)
  - ◆ 150Mbps (≥ 1.1V to 1.5V Translation)
  - ◆ 100Mbps (≥ 1.1V to 1.2V Translation)
- Outputs in High-Impedance State when V<sub>CCA</sub> or V<sub>CCB</sub> = 0V
- -40°C to +125°C Operating Temperature Range
- Available in a Green TSSOP-16 Package

## APPLICATIONS

Personal Electronic  
Industrial Equipment  
Enterprise Infrastructures  
Telecom Equipment

# 4-Bit Dual-Supply Translating Transceiver with 74AVC4T245 Configurable Voltage Translation and 3-State Outputs


## PACKAGE/ORDERING INFORMATION

MODEL	PACKAGE DESCRIPTION	SPECIFIED TEMPERATURE RANGE	ORDERING NUMBER	PACKAGE MARKING	PACKING OPTION
74AVC4T245	TSSOP-16	-40°C to +125°C	74AVC4T245XTS16G/TR	03R XTS16 XXXXX	Tape and Reel, 4000

## MARKING INFORMATION

NOTE: XXXXX = Date Code, Trace Code and Vendor Code.

**XXXXX**



Green (RoHS & HSF): SG Micro Corp defines "Green" to mean Pb-Free (RoHS compatible) and free of halogen substances. If you have additional comments or questions, please contact your SGMICRO representative directly.

## ABSOLUTE MAXIMUM RATINGS <sup>(1)</sup>

Supply Voltage Range, $V_{CCA}$ .....	-0.5V to 4.6V
Supply Voltage Range, $V_{CCB}$ .....	-0.5V to 4.6V
Input Voltage Range, $V_I$ <sup>(2)</sup> .....	-0.5V to 4.6V
Output Voltage Range, $V_O$ <sup>(2)</sup>	
Suspend or 3-State Mode .....	-0.5V to 4.6V
Active Mode	
A Ports .....	-0.5V to MIN (4.6V, $V_{CCA} + 0.5V$ )
B Ports .....	-0.5V to MIN (4.6V, $V_{CCB} + 0.5V$ )
Output Current, $I_O$ ( $V_O = 0V$ to $V_{CC}$ )	
High-State or Low-State .....	$\pm 50mA$
Supply Current, $I_{CC}$ , per $V_{CCA}$ or $V_{CCB}$ Pin .....	100mA
Ground Current, $I_{GND}$ , per GND Pin .....	-100mA
Input Clamp Current, $I_{IK}$ ( $V_I < 0$ ).....	-50mA
Output Clamp Current, $I_{OK}$ ( $V_O < 0$ ).....	-50mA
Junction Temperature <sup>(3)</sup> .....	+150°C
Storage Temperature Range .....	-65°C to +150°C
Lead Temperature (Soldering, 10s).....	+260°C
ESD Susceptibility	
HBM.....	6000V
CDM .....	1000V

## RECOMMENDED OPERATING CONDITIONS

Supply Voltage Range, $V_{CCA}$ .....	0.8V to 3.6V
Supply Voltage Range, $V_{CCB}$ .....	0.8V to 3.6V
Input Voltage Range, $V_I$ .....	0V to 3.6V
Output Voltage Range, $V_O$	
Suspend or 3-State Mode .....	0V to 3.6V
Active Mode	
A Ports .....	0V to $V_{CCA}$
B Ports .....	0V to $V_{CCB}$
High-State or Low-State Output Current, $I_O$ .....	$\pm 12mA$

Input Transition Rise or Fall Rate,  $\Delta t/\Delta V$

$V_{CCI} = 0.8V$  to 3.6V ..... 5ns/V (MAX)

Operating Temperature Range..... -40°C to +125°C

## OVERSTRESS CAUTION

- Stresses beyond those listed in Absolute Maximum Ratings may cause permanent damage to the device. Exposure to absolute maximum rating conditions for extended periods may affect reliability. Functional operation of the device at any conditions beyond those indicated in the Recommended Operating Conditions section is not implied.
- The minimum input voltage ratings and output voltage ratings may be exceeded if the input and output current ratings are observed.
- The performance capability of a high-performance integrated circuit in conjunction with its thermal environment can create junction temperatures which are detrimental to reliability.

## ESD SENSITIVITY CAUTION


This integrated circuit can be damaged if ESD protections are not considered carefully. SGMICRO recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage. ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because even small parametric changes could cause the device not to meet the published specifications.

## DISCLAIMER

SG Micro Corp reserves the right to make any change in circuit design, or specifications without prior notice.

# 74AVC4T245 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

## LOGIC DIAGRAM



## FUNCTION TABLE

SUPPLY VOLTAGE	CONTROL INPUT		INPUT/OUTPUT	
$V_{CCA}, V_{CCB}^{(1)}$	$\overline{nOE}$	nDIR	nAn	nBn
0.8V to 3.6V	L	L	nAn = nBn	Inputs
0.8V to 3.6V	L	H	Inputs	nBn = nAn
0.8V to 3.6V	H	X	Z	Z
GND <sup>(2)</sup>	X	X	Z	Z


H = High Voltage Level  
 L = Low Voltage Level  
 Z = High-Impedance State  
 X = Don't Care

### NOTES:

- The nAn, nDIR and  $\overline{nOE}$  signals are referenced to  $V_{CCA}$ . The nBn signals are referenced to  $V_{CCB}$ .
- If at least one of  $V_{CCA}$  or  $V_{CCB}$  is at GND level, the device enters suspend mode.

# 74AVC4T245 4-Bit Dual-Supply Translating Transceiver with Configurable Voltage Translation and 3-State Outputs

## PIN CONFIGURATION




## PIN DESCRIPTION


PIN	NAME	FUNCTION
1	$V_{CCA}$	Supply Voltage $V_{CCA}$ . The $nA_n$ , $nDIR$ and $n\overline{OE}$ signals are referenced to $V_{CCA}$ .
2, 3	1DIR, 2DIR	Direction Control Inputs.
4, 5	1A1, 1A2	Data Inputs/Outputs.
6, 7	2A1, 2A2	Data Inputs/Outputs.
8, 9	GND	Ground.
11, 10	2B1, 2B2	Data Inputs/Outputs.
13, 12	1B1, 1B2	Data Inputs/Outputs.
15, 14	$1\overline{OE}$ , $2\overline{OE}$	Output Enable Inputs (Active Low).
16	$V_{CCB}$	Supply Voltage $V_{CCB}$ . The $nB_n$ signals are referenced to $V_{CCB}$ .

PACKAGE OUTLINE DIMENSIONS

TSSOP-16



RECOMMENDED LAND PATTERN (Unit: mm)



Symbol	Dimensions In Millimeters		
	MIN	MOD	MAX
A	-	-	1.200
A1	0.050	-	0.150
A2	0.800	-	1.050
b	0.190	-	0.300
c	0.090	-	0.200
D	4.860	-	5.100
E	4.300	-	4.500
E1	6.200	-	6.600
e	0.650 BSC		
L	0.450	-	0.750
H	0.250 TYP		
θ	0°	-	8°
ccc	0.100		


NOTES:

1. This drawing is subject to change without notice.
2. The dimensions do not include mold flashes, protrusions or gate burrs.
3. Reference JEDEC MO-153.


# PACKAGE INFORMATION

## TAPE AND REEL INFORMATION

### REEL DIMENSIONS



### TAPE DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.


### KEY PARAMETER LIST OF TAPE AND REEL

Package Type	Reel Diameter	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P0 (mm)	P1 (mm)	P2 (mm)	W (mm)	Pin1 Quadrant
TSSOP-16	13"	12.4	6.80	5.40	1.50	4.0	8.0	2.0	12.0	Q1

DD0001

# PACKAGE INFORMATION

## CARTON BOX DIMENSIONS



NOTE: The picture is only for reference. Please make the object as the standard.

## KEY PARAMETER LIST OF CARTON BOX

Reel Type	Length (mm)	Width (mm)	Height (mm)	Pizza/Carton
13"	386	280	370	5

DD0002